

# Graph Neural Team Recommendation: An Integrated Approach

Anonymous Author(s)

## Abstract

Team recommendation aims to select an optimal subset of experts that can form an *almost surely* successful collaborative team for a given set of required skills. State-of-the-art methods are neural multi-label classifiers that *transfer* dense vector representations of skills into a sparse occurrence vector representing the optimal subset of experts. Such methods, however, overlook experts' relational and structural information encoded in the expert collaboration graph and, thus, fall short of capturing complex inter-dependencies among experts and their associated skills within teams. Moreover, the skills' dense vectors are pretrained *disjointly* and independently of the underlying neural classifier, hence, preventing end-to-end optimization. In this paper, we propose to reformulate the team recommendation problem into *end-to-end* link predictions between expert nodes and the required skill nodes in the expert collaboration graph to consume multi-hop intra-team and cross-team collaborations among experts while eschewing the unnecessary complexities of the disjoint two-phase training procedure. Our experiments on two large-scale datasets from various domains with distinct distributions of skills in teams demonstrate the superiority of our proposed approach and establish a new state of the art.<sup>1</sup>

## CCS Concepts

• **Human-centered computing** → *Social recommendation*.

## Keywords

Neural Team Recommendation; Social Information Retrieval;

## 1 Introduction

Collaborative teamwork has become paramount in diverse real-world settings, including health care [32, 40], scientific peer review [1, 2, 29], and education [5, 33], where combined skills applied in coordinated ways can solve difficult tasks. As a result, forming teams of experts whose success is *almost surely* guaranteed has been a surge of research for years to replace the tedious, error-prone, and suboptimal manual search process; from operations research [4, 12, 13, 23, 42, 45, 49, 51], social network analysis [17, 24, 41], and more recently, machine learning [7, 15, 35, 37]. Specifically, neural models [7, 8, 34, 35, 38, 39] have brought state-of-the-art efficacy while enhancing efficiency due to the iterative learning procedure and availability of training datasets. Neural models, by and large, frame the team recommendation problem as a *multi-label* Boolean classification task and learn the vector representations of experts and their skills in a training dataset of successful and (virtually) unsuccessful teams to draw future teams that are, more likely than not, successful. Such work, however, was premised on the mutually independent selection of teams from a training set, overlooking the fact that a team is indeed inherently relational, and its success depends on the intra- and cross-team collaborations among experts.

<sup>1</sup>The codebase is publicly available; however, we omit the link for double-blind review. The implementation is part of a unified framework that cannot be fully anonymized.



**Figure 1: Multi-hop relations and structure in the expert collaboration graph (left). Our end-to-end approach (right).**

In this paper, we propose to model collaborative ties of experts within and across teams in a graph and leverage graph neural networks to capture multi-hop relational and structural information encoded in the graph for complex inter-dependencies among experts and their associated skills within teams, as shown in Figure 1. We then propose to reformulate the team recommendation problem into end-to-end link predictions between nodes of required skills and optimal experts for a team node directly within the graph. Given a successful team, we map it into a connected *star* subgraph that connects the team's node to its required subset of skills and expert members. After incorporating all successful teams of a training set in the graph, we then apply a graph neural network to learn dense vectors of skills and experts jointly based on link prediction loss among positive (existing) and negative (non-existing) link sampling strategies. During inference, given a test team with its subset of required skills yet *unseen* expert members, as shown in Figure 1 (right), we use the graph neural network to predict links between expert nodes and the team's node and select the top- $k$  highest probable experts as the recommended team of size  $k$ .

While employing graphs to model experts' collaborations was mainstream in traditional team recommendation approaches rooted in subgraph optimization [17, 24, 41], existing neural-based methods have leveraged graphs only for prior pretraining and the *transfer* of dense vectors of skills to accommodate a large set of skills and reduce the complexity of the neural architectures in the input layer [26, 34, 35]. For instance, Rad et al. [35] used `metapath2vec` [10] on a skill-team-expert tripartite graph to pretrain and transfer skill embeddings as the input for a variational Bayesian neural classifier [35]. Alternatively, Kaw et al. [26] employed deep graph infomax [44], an unsupervised graph convolutional network that maximizes mutual information between local node-level representations and global summary representation of the entire graph, for more effective embeddings of skills. Such approaches, however, entail key shortcomings: (1) foremost, they overlook the multi-hop relational and structural information among experts and their collaborations within and across teams in the graph; (2) the skill vectors are learned *disjointly* in a self-supervised manner during a pretraining phase, oblivious to the team recommendation learning process; (3) they suffer from independent selection of teams from the training set by the underlying neural classifiers.

Inspired by the efficacy of end-to-end graph neural networks in various recommendation and information retrieval tasks [6, 14, 16, 20, 21, 27, 31, 46, 47, 52], yet unexplored in team recommendation, our approach fills the gaps by capturing multi-hop relational and structural information not only for skills but also for experts and

teams directly in the expert collaboration graph, thereby recommending more effective teams as evidenced by our experiments, including 3 different graph structures, 6 strong graph neural networks, and 2 large-scale datasets from diverse domains with varied distributions of teams over skills.

## 2 Problem Definition

Given a set of skills  $\mathcal{S} = \{s_i\}$  and a set of experts  $\mathcal{E} = \{e_j\}$ , a team  $t$  is a subset of experts  $\mathbf{e} \subseteq \mathcal{E}$  that collectively cover a subset of skills  $\mathbf{s} \subseteq \mathcal{S}$  with its success status  $y \in \{0, 1\}$ , denoted by  $t_{\mathbf{s}, \mathbf{e}, y}$ . Further,  $\mathcal{T} = \mathcal{T}^+ \cup \mathcal{T}^- = \{t_{\mathbf{s}, \mathbf{e}, y=1}\} \cup \{t_{\mathbf{s}, \mathbf{e}, y=0}\}$  is the set of successful and unsuccessful teams. For a subset of skills  $\mathbf{s}$ , a neural team recommender aims to identify an optimal subset of experts  $\mathbf{e}$  such that their collaboration results in a successful team, i.e.,  $t_{\mathbf{s}, \mathbf{e}, y=1}$ , while avoiding any subset  $\mathbf{e}'$  that leads to an unsuccessful team, i.e.,  $t_{\mathbf{s}, \mathbf{e}', y=0}$ . Specifically, the objective is to learn a mapping function  $f$ , parameterized by  $\theta$ , such that  $\forall t \in \mathcal{T}^+$ :  $f_\theta(\mathbf{s}) = \mathbf{e}$ .

## 3 Preliminaries

The state of the art [7, 26, 34, 35, 37] estimate  $f_\theta(\mathbf{s}) = \mathbf{e}$  using a neural multi-label Boolean classifier that transfers the *dense* vector representation of a subset of skills,  $v_{\mathbf{s}} \in \mathbb{R}^d$ , to the occurrence (multi-hot) vector representation of the optimal (successful) subset of experts,  $v_{\mathbf{e}} \in \{0, 1\}^{|\mathcal{E}|}$ , i.e.,  $f_\theta(v_{\mathbf{s}}) = v_{\mathbf{e}}$ , by maximizing the posterior probability of  $\theta$  in  $f_\theta$  over  $\mathcal{T}^+$  in a variational Bayesian neural architecture via minimizing Kullback-Leibler divergence [30].

To transfer dense vector representation of a subset of skills  $v_{\mathbf{s}}$ , they construct a heterogeneous tripartite graph  $\mathbb{G} = \langle \mathcal{N}, \mathcal{L} \rangle$  whose nodes are skills  $n_{\mathcal{S}}$ , successful teams  $n_{\mathcal{T}^+}$  and experts  $n_{\mathcal{E}}$ , i.e.,  $\mathcal{N} = n_{\mathcal{S}} \cup n_{\mathcal{T}^+} \cup n_{\mathcal{E}}$ , and links are undirected  $\mathcal{L} = \{n_{\mathcal{S}} \times n_{\mathcal{T}^+}\} \cup \{n_{\mathcal{T}^+} \times n_{\mathcal{E}}\}$ . From Figure 1 (right), each team  $t_{\mathbf{s}, \mathbf{e}, y=1} \in \mathcal{T}^+$  is represented by a star subgraph with a team node as the central node and its required skills  $\mathbf{s}$  and expert members  $\mathbf{e}$  are the leaves, connected to the team node but not to each other. Then, a graph neural network  $g$ , parameterized by  $\phi$ , is trained such that  $g_\phi : \mathcal{N} \rightarrow \mathbb{R}^d$ ,  $g_\phi(n_{s_i}) = v_{s_i}$ . Finally, the dense vector of the required subset of skills  $\mathbf{s}$  for a team  $t_{\mathbf{s}, \mathbf{e}, y}$  is obtained by summing the vectors of its constituent skill nodes, i.e.,  $v_{\mathbf{s}} = \sum_{s_i \in \mathbf{s}} v_{s_i} = \sum_{s_i \in \mathbf{s}} g_\phi(n_{s_i})$ .

**Limitations:**  $g_\phi$  is estimated to capture structural and semantic information of skills only, completely disregarding the expert and their multi-hop collaborations within the context of historically successful teams. Moreover, it is *prior* to and *disjoint* from the main team recommendation task and is kept constant and oblivious to the multi-label classification loss when estimating  $f_\theta$ . Finally, the estimation of  $f_\theta$ , the primary predictor, relies on the mutually independent selection of teams from the training set.

## 4 Proposed Approach

We propose to estimate  $f$  directly through the link prediction loss among team-expert links by  $g_\phi$  on the expert collaboration graph, eliminating  $\theta$  and the multi-label classifier. Following the standard message passing formulation and without loss of generality to modern graph neural networks,  $g_\phi(n)$  denotes the vector representation of a node  $n \in \mathcal{N}$  at layer (hop)  $l$ , and computed as:

$$g_\phi(n) = \mathbf{h}_n^l = \phi_{update} \left( \mathbf{h}_n^{(l-1)}, \sum_{i \in \mathcal{N}_n \subseteq \mathcal{N}} \phi_{message} \left( \mathbf{h}_n^{(l-1)}, \mathbf{h}_i^{(l-1)} \right) \right) \quad (1)$$

where  $\mathbf{h}_n^{l=0}$  denotes the randomly initialized vectors for the node  $n$ ,  $\mathcal{N}_n$  is the set of neighboring nodes of  $n$ ,  $\phi_{message}$  are learnable parameters for a message function to process the neighbors' vectors prior to aggregation, and ranges from a simple identity function to a more expressive multilayer perceptron with attention coefficients over neighboring nodes, as in `gat` [43]. Similarly,  $\phi_{update}$  denotes the learnable parameters of an update function that computes the node vector  $\mathbf{h}_n^l$  by combining its previous vector  $\mathbf{h}_n^{(l-1)}$  with the aggregated vectors from its neighborhood, and can be as simple as summation, or another multilayer perceptron, as in `gin` [50]. The complete set of parameters is given by  $\phi = \phi_{update} \cup \phi_{message}$ , which are learned by minimizing a link prediction loss over observed team-expert links of all successful teams, i.e.,  $\forall t_{\mathbf{s}, \mathbf{e}, y=1} \in \mathcal{T}^+, \forall e_j \in \mathbf{e}$ :

$$\sum_{(n_{\mathbf{s}}, n_{e_j}) \in \mathcal{L}} -\log \sigma \left( g_\phi(n_{t_{\mathbf{s}, \mathbf{e}, y=1}})^\top g_\phi(n_{e_j}) \right) = \sum_{(n_{\mathbf{s}}, n_{e_j}) \in \mathcal{L}} -\log \sigma \left( [\mathbf{h}_{n_{\mathbf{s}}}^l]^\top [\mathbf{h}_{n_{e_j}}^l] \right) \quad (2)$$

where  $\sigma$  is the sigmoid function, predicting the presence of links between a successful team and its expert members. While Eq. 1 leverages *all* types of links for message passing irrespective of their semantic roles, capturing heterogeneous relational and structural information, Eq. 2 explicitly uses this information to supervise the primary task of team-expert link prediction for recommending successful teams. During inference, as shown in Figure 1 (right), for a team  $t_{\mathbf{s}, *, y=1}$  with a subset of required skills  $\mathbf{s}$  yet *unknown* expert members, we use the learned  $g_\phi$  to predict links between the team node  $n_t$  and all candidate expert nodes  $n_{\mathcal{E}}$ . Specifically, for each expert  $e \in \mathcal{E}$ , we compute:

$$f_\theta(\mathbf{s}) \simeq f(\mathbf{s}; \mathbb{G}, g_\phi) = \sigma \left( g_\phi(n_{t_{\mathbf{s}, *, y=1}})^\top g_\phi(n_e) \right) = \sigma \left( [\mathbf{h}_{n_{t_{\mathbf{s}, *, y=1}}}^l]^\top [\mathbf{h}_{n_e}^l] \right) \quad (3)$$

and select the subset of experts with the top- $k$  predicted probabilities as the recommended team of size  $k$ .

Our proposed end-to-end formulation directly taps into multi-hop relational and structural information encoded in the graph for complex intra-team and cross-team interactions and dependencies among experts and their associated skills, as shown in Figure 1 (left); a capacity in which neural classifiers are inherently limited. Moreover, it avoids two disjoint learning stages with separate parameter sets, i.e., the pretraining of  $g_\phi$  and the subsequent fine-tuning for  $f_\theta$ . Herein,  $\phi$  is the sole learnable set of parameters.

## 5 Experiments

In this section, we seek to answer our main research question:

**RQ1:** Does the end-to-end approach outperform the transfer-based approach for team recommendation? If affirmative, we further ask:

**RQ2:** Is RQ1's answer consistent across datasets from varied domains with distinct distributions of teams over skills?

**RQ3:** Is RQ1's answer consistent across different graph structures?


**RQ4:** Which graph neural network performs the best (worst) in the end-to-end vs. transfer-based approaches for team recommendation?

### 5.1 Datasets

We used two benchmark datasets as in prior works [7, 25, 28, 36, 37]: **dblp**, a collection of computer science publications [9], where a *published* paper is a successful team, the authors are the expert members, and the keywords are the required skills, and **imdb**, a

**Table 1: Statistics of the raw and preprocessed datasets.**

|                       | dblp          |               | imdb         |           |
|-----------------------|---------------|---------------|--------------|-----------|
| teams $\mathcal{T}$   | publications  |               | movies       |           |
| experts $\mathcal{E}$ | authors       |               | cast & crew  |           |
| skills $\mathcal{S}$  | keywords      |               | (sub) genres |           |
| success $y$           | published     |               | produced     |           |
| statistics            | raw           | filtered      | raw          | filtered  |
| $ \mathcal{T} $       | 4,877,383     | 99,375        | 507,034      | 32,059    |
| $ \mathcal{E} $       | 5,022,955     | 14,214        | 876,981      | 2,011     |
| $ \mathcal{S} $       | <b>89,504</b> | <b>29,661</b> | <b>28</b>    | <b>23</b> |



**Figure 2: Distribution of teams over experts and skills.**

collection of movies [22], where a *produced* movie is considered as a successful team, the cast and crew are the experts, and the movie’s genres and subgenres are the required skills. In contrast to movie recommenders or movie review analysis, herein, the objective is to form a team for a successful movie production.

Teams with fewer than 3 expert members were removed while ensuring no alteration to the statistical distributions, as detailed in Table 1. From Figure 2 (left), both datasets exhibit long-tailed distributions of teams over experts, i.e., few dominant experts have contributed to many teams, while the majority have participated scarcely. Regarding skills, from Figure 2 (right), while dblp follows a similar long-tail distribution of teams over skills, imdb demonstrates a more uniform distribution across a limited set of skills (genres), which are consistently used in many movies.

## 5.2 Baselines

We compared the end-to-end approach (e2e-\*) with the following transfer-based (t-\*) baselines:

**t-bnn.m2v** [35]: It is the pioneer to transfer embeddings of skills by metapath2vec [10] for a variational Bayesian neural classifier.

**t-bnn.lant** [26]: It employs deep graph infomax [44] for more effective embeddings of skills in fewer training epochs.

To ensure a comprehensive comparison between the end-to-end and transfer-based approaches, we also included strong graph neural networks for a heterogeneous graph<sup>2</sup>:

**graphsage (gs)** [18]: It aggregates neighbours’ vectors by a fixed function, herein, mean, followed by concatenation with the node’s current vector.


**gin** [50]: It learns node vectors via *learnable* aggregation and combination functions, which, theoretically, show the best node embeddings by capturing graph structure based on the Weisfeiler-Lehman graph isomorphism test [11].

**gine** [19]: It extends gin to include global graph features based on a subgraph of neighbors located between  $k_1$ -hop and  $k_2$ -hop of a node where  $k_1 < k_2$ , and is designed to utilize link features.

**gat** [43]: It aggregates neighbors with *learnable* multi-head attention scores based on the importance of neighbors when aggregating and combining vectors during message passing.

**gatv2** [3]: As opposed to gat, which computes pairwise attention between a node and its neighbors using shared parameters, it uses a different set of parameters for a node and each of its neighbors that are updated through layers (hops).

<sup>2</sup>torch\_geometric.nn.conv.HeteroConv.html



**Figure 3: Impact of neighborhood sampling.**

**han** [48]: It is a hierarchical gat that captures the importance of different node types and their predefined meta-paths to neighbours.

All graph neural networks included convolutional layers of size 64 and relu activation, after a search over different sizes of {16, 32, 64, 128, 256} across dblp and imdb datasets. For message passing, all neighbors were considered with a negative sampling at a ratio of 5:1. We employed 1-hop sampling with 20 nodes, 2-hop sampling with [20, 10], i.e., 20 and 10 nodes in the first and second hops, and 3-hop sampling with [20, 10, 5] and [30, 20, 10]. From Figure 3, we observed generally favorable results with 2-hop sampling and [20, 10], though not uniformly across all models. All graph neural networks were trained for 5 epochs in batch sizes of 125 with a learning rate of 0.001 using Adam. For the transfer-based, we cross-compare variational Bayesian (t-bnn-\*) and non-variational (t-fnn-\*) neural classifiers, following their settings in [35, 36].

## 5.3 Evaluation Strategy and Metrics

We used the entire dataset to create the expert collaboration graph. For the test set, we selected 15% of the randomly shuffled teams and removed their team-expert links  $(n_t, n_e) \in \mathcal{L}$  to mask the expert members as *unseen* during training. Given a team  $t_{s,e,y=1}$  from the test set, a trained model infers the membership probability of all experts by team-expert link predictions. We selected the top- $k \in \{5, 10\}$  experts as the recommended team and compared them against the ground-truth expert set  $\mathbf{e}$  and reported precision (pr), recall (rec), normalized discounted cumulative gain (ndcg), and mean average precision (map), averaged over the test set.

## 6 Results

**RQ1: End-to-end vs. transfer-base approach.** From Table 2, we observe that the end-to-end approach (e2e-\*) consistently and substantially outperforms *all* transfer-based methods using either t-fnn-\* or t-bnn-\* classifiers across all employed graph neural networks, datasets, and metrics. The superiority of the end-to-end approach lies in leveraging both multi-hop relational and structural information in the expert collaboration and supervised information about the optimal subset of experts within successful teams.

**RQ2: Cross-domain performance consistency.** From Table 2, we can observe that the performance improvement by graph neural networks is consistent for both datasets in our end-to-end approach. However, in the transfer-based approach, the performance varies in variational and non-variational models with *no* consistent trend based on their underlying graph neural network for different datasets. Yet, attentive models, t-\*han, t-\*gat, or t-\*gatv2, generally stand out as the top-performers.

**RQ3: Cross-graph structural performance consistency.** To study the impact of graph structure, we considered i) skill-team-expert-**location** where a team is further connected to its location, and ii) skill-expert bipartite graph, consisting of links between skills and expert members of a team but with *no* node for the team.

Table 2: Efficacy of end-to-end vs. transfer-based approaches in dblp and imdb using skill-team-expert graph structure.

|       |       | dblp         |              |              |              |              |              |              |              | imdb         |              |              |              |              |              |              |              |
|-------|-------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
|       |       | %pr          |              | %rec         |              | %ndcg        |              | %map         |              | %pr          |              | %rec         |              | %ndcg        |              | %map         |              |
| k     |       | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          |
| e2e   | gs    | 14.37        | 09.24        | 54.00        | 67.79        | 33.21        | 38.39        | 25.18        | 28.10        | 15.39        | 09.16        | 49.73        | 57.44        | 33.70        | 36.78        | 27.00        | 29.03        |
|       | gin   | 14.47        | 09.07        | 54.68        | 66.95        | 31.50        | 36.12        | 22.74        | 25.36        | 14.08        | 08.91        | 45.34        | 56.49        | 28.49        | 32.79        | 21.76        | 24.30        |
|       | gine  | 07.66        | 07.65        | 21.56        | 44.17        | 16.50        | 24.74        | 12.67        | 16.18        | 19.33        | 12.21        | 53.14        | 66.25        | 38.80        | 43.86        | 31.13        | 34.07        |
|       | gat   | 14.33        | 09.46        | 53.81        | 68.86        | 38.11        | 43.78        | 31.44        | 34.65        | 14.66        | 09.17        | 47.44        | 57.47        | 33.45        | 37.40        | 27.17        | 29.68        |
|       | gatv2 | 14.03        | 09.48        | 52.73        | 69.01        | 37.87        | 43.98        | 31.43        | 34.86        | 14.49        | 09.09        | 46.72        | 57.18        | 33.81        | 37.88        | 27.86        | 30.39        |
|       | han   | <b>28.97</b> | <b>15.17</b> | <b>83.19</b> | <b>86.38</b> | <b>70.42</b> | <b>71.74</b> | <b>64.28</b> | <b>65.27</b> | <b>23.37</b> | <b>15.42</b> | <b>57.82</b> | <b>74.15</b> | <b>45.58</b> | <b>52.38</b> | <b>37.42</b> | <b>42.21</b> |
| t-fnn | m2v   | 00.82        | 00.70        | 01.24        | 02.13        | 01.13        | 01.55        | 00.66        | 00.82        | 00.84        | 00.77        | 00.95        | 01.76        | 00.95        | 01.33        | 00.46        | 00.57        |
|       | lant  | 00.90        | 00.83        | 01.35        | 02.48        | 01.17        | 01.69        | 00.67        | 00.84        | 00.74        | 00.68        | 00.81        | 01.52        | 00.85        | 01.18        | 00.40        | 00.50        |
|       | gs    | 00.87        | 00.74        | 01.30        | 02.24        | 01.26        | 01.63        | 00.60        | 00.76        | 00.83        | 00.73        | 00.91        | 01.64        | 00.95        | 01.27        | 00.44        | 00.55        |
|       | gin   | 00.95        | 00.78        | 01.43        | 02.35        | 01.37        | 01.57        | 00.59        | 00.76        | 00.76        | 00.68        | 00.84        | 01.56        | 00.87        | 01.19        | 00.40        | 00.51        |
|       | gine  | 01.02        | 00.83        | 01.52        | 02.49        | 01.35        | 01.80        | 00.76        | 00.92        | 00.73        | 00.64        | 00.82        | 01.45        | 00.85        | 01.14        | 00.41        | 00.50        |
|       | gat   | 01.19        | 00.92        | 01.78        | 02.75        | 01.62        | 02.08        | 00.92        | 01.09        | 00.92        | 00.82        | 01.00        | 01.83        | 01.06        | 01.43        | 00.50        | 00.62        |
| t-bnn | gatv2 | 01.01        | 00.83        | 01.51        | 02.51        | 01.41        | 01.88        | 00.80        | 00.96        | 00.87        | 00.80        | 00.96        | 01.80        | 00.98        | 01.37        | 00.47        | 00.59        |
|       | han   | 00.93        | 00.82        | 01.42        | 02.49        | 01.33        | 01.82        | 00.80        | 00.97        | 00.77        | 00.72        | 00.86        | 01.63        | 00.85        | 01.21        | 00.39        | 00.50        |
|       | m2v   | 00.31        | 00.32        | 00.48        | 00.98        | 00.42        | 00.65        | 00.23        | 00.30        | 00.76        | 00.71        | 00.83        | 01.58        | 00.85        | 01.20        | 00.41        | 00.52        |
|       | lant  | 00.66        | 00.61        | 01.01        | 01.87        | 00.88        | 01.28        | 00.49        | 00.61        | 01.01        | 00.96        | 01.14        | 02.18        | 01.18        | 01.66        | 00.58        | 00.73        |
|       | gs    | 00.71        | 00.66        | 01.08        | 02.00        | 00.94        | 01.36        | 00.52        | 00.65        | 00.99        | 00.90        | 01.12        | 02.03        | 01.12        | 01.55        | 00.54        | 00.67        |
|       | gin   | 00.60        | 00.52        | 00.91        | 01.59        | 00.84        | 01.15        | 00.49        | 00.60        | 00.90        | 00.83        | 01.04        | 01.92        | 01.07        | 01.47        | 00.52        | 00.65        |
| t-bnn | gine  | 00.75        | 00.63        | 01.12        | 01.90        | 01.08        | 01.44        | 00.66        | 00.79        | 01.01        | 00.93        | 01.15        | 02.14        | 01.16        | 01.62        | 00.58        | 00.71        |
|       | gat   | 00.66        | 00.62        | 00.99        | 01.86        | 00.87        | 01.28        | 00.49        | 00.62        | 00.96        | 00.86        | 01.07        | 01.94        | 01.10        | 01.50        | 00.53        | 00.66        |
|       | gatv2 | 00.64        | 00.54        | 00.96        | 01.64        | 00.87        | 01.19        | 00.49        | 00.58        | 00.93        | 00.80        | 01.05        | 01.84        | 01.05        | 01.41        | 00.51        | 00.62        |
|       | han   | 00.80        | 00.71        | 01.20        | 02.15        | 01.09        | 01.53        | 00.61        | 00.76        | 01.06        | 00.99        | 01.19        | 02.25        | 01.21        | 01.70        | 00.59        | 00.74        |

Table 3: Efficacy of approaches using location in dblp.

|       |       | %pr          |              | %rec         |              | %ndcg        |              | %map         |              |
|-------|-------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| k     |       | @5           | @10          | @5           | @10          | @5           | @10          | @5           | @10          |
| e2e   | gs    | 14.63        | 09.15        | 52.91        | 64.97        | 35.37        | 39.90        | 28.27        | 30.88        |
|       | gin   | 11.80        | 08.78        | 42.44        | 62.46        | 26.28        | 33.65        | 19.51        | 23.54        |
|       | gat   | 13.69        | <b>09.39</b> | 50.24        | <b>66.50</b> | 35.57        | 41.74        | 29.10        | 32.62        |
|       | gatv2 | <b>15.46</b> | 09.22        | <b>56.15</b> | 65.38        | <b>42.58</b> | <b>46.13</b> | <b>36.62</b> | <b>38.75</b> |
|       | han   | 06.77        | 07.93        | 13.90        | 29.40        | 13.85        | 20.50        | 10.15        | 13.39        |
|       | t-fnn | gs           | 00.54        | 00.54        | 00.82        | 01.65        | 00.71        | 01.10        | 00.38        |
| gin   |       | 00.94        | 00.80        | 01.43        | 02.44        | 01.28        | 01.75        | 00.73        | 00.88        |
| gat   |       | 00.77        | 00.70        | 01.18        | 02.12        | 01.04        | 01.47        | 00.57        | 00.71        |
| gatv2 |       | 00.96        | 00.79        | 01.45        | 02.40        | 01.25        | 01.69        | 00.69        | 00.83        |
| han   |       | 00.92        | 00.79        | 01.38        | 02.36        | 01.26        | 01.72        | 00.72        | 00.87        |
| t-bnn |       | gs           | 00.85        | 00.73        | 01.28        | 02.20        | 01.14        | 01.56        | 00.64        |
|       | gin   | 00.46        | 00.42        | 00.70        | 01.27        | 00.62        | 00.89        | 00.34        | 00.42        |
|       | gat   | 00.59        | 00.53        | 00.90        | 01.61        | 00.81        | 01.14        | 00.46        | 00.57        |
|       | gatv2 | 00.52        | 00.52        | 00.77        | 01.56        | 00.67        | 01.04        | 00.37        | 00.48        |
|       | han   | 00.62        | 00.58        | 00.94        | 01.76        | 00.81        | 01.19        | 00.44        | 00.56        |

Following the literature [35], we set the location of a team in dblp as the publication venue. In imdb, however, the available location information is the producing country of a movie, which is US in almost all movies, and was therefore omitted from our experiments. From Tables 2 and 3, we observe that the performance of e2e-\* models on the expert collaboration graph with location and lack thereof is closely aligned, with marginal differences, except for han, which is no longer the best due to its meta-path-based attention mechanism that overlooked the location links. In contrast, for transfer-based models, we observe little to no improvement, which is expected as the vector representations of skills are insufficient to convey such additional information to neural classifiers. In the skill-expert bipartite graph, from Table 4 including top-performing baselines, we observe that neither end-to-end nor transfer-based models perform on par with their performance in other graph structures due to the highly dense bipartite graph structure, wherein all skills and experts are connected to each other without the contextual separation by team nodes, which highlights the importance of graph structure in effective message passing in graph neural networks.

**RQ4: Performance leaderboard for graph neural networks.** From Table 2 and for the end-to-end approach, it is evident that

Table 4: Inefficacy of skill-expert graph structure.

|        |     | dblp  |       |       |       | imdb  |       |       |       |
|--------|-----|-------|-------|-------|-------|-------|-------|-------|-------|
| k = 10 |     | %pr   | %rec  | %ndcg | %map  | %pr   | %rec  | %ndcg | %map  |
| e2e    | gs  | 00.04 | 00.15 | 00.08 | 00.04 | 00.13 | 00.42 | 00.28 | 00.14 |
|        | gat | 00.03 | 00.13 | 00.07 | 00.03 | 00.21 | 00.64 | 00.39 | 00.16 |
|        | han | 00.05 | 00.18 | 00.10 | 00.04 | 00.15 | 00.49 | 00.32 | 00.15 |
| t-fnn  | m2v | 00.80 | 02.44 | 01.83 | 00.99 | 00.73 | 01.64 | 01.26 | 00.54 |
|        | gs  | 00.83 | 02.51 | 01.46 | 00.71 | 00.75 | 01.70 | 01.31 | 00.56 |
|        | gat | 00.85 | 02.57 | 01.92 | 00.98 | 00.65 | 01.46 | 01.15 | 00.50 |
| t-bnn  | han | 00.84 | 02.54 | 01.81 | 00.95 | 00.73 | 01.61 | 01.25 | 00.53 |
|        | m2v | 00.39 | 01.20 | 00.83 | 00.40 | 00.89 | 02.04 | 01.56 | 00.69 |
|        | gs  | 00.58 | 01.75 | 01.22 | 00.59 | 00.96 | 02.18 | 01.61 | 00.68 |
| t-bnn  | gat | 00.53 | 01.60 | 01.06 | 00.49 | 01.01 | 02.31 | 01.74 | 00.76 |
|        | han | 00.51 | 01.54 | 01.05 | 00.51 | 00.94 | 02.15 | 01.64 | 00.72 |

han outperforms all methods across datasets and metrics, with gat and gatv2 being the closest runners-up in dblp. The consistent high performance of han, gat, and gatv2 highlights the dominance of attention-based graph neural networks. In contrast, despite the gin model’s theoretically proven efficacy in capturing graph structure [50], its empirical performance typically lags behind the attentive models for its sensitivity to hyperparameters. With respect to the transfer-based approach, not unexpectedly, we observe a consistent efficacy of graph neural networks compared to naive embeddings of skills (mhot). Attentive models (gat, gatv2) generally perform the best, similarly when employed in the end-to-end approach. However, the performance ranking of graph neural networks is inconsistent across neural classifiers; it is more stable for non-variational models (t-fnn-\*) than for variational ones (t-bnn-\*) due to the greater sensitivity of variational architectures.

## 7 Concluding Remarks and Future Work

In this paper, we proposed an end-to-end graph neural network to improve the efficacy of team recommendations. Our experiments on two large-scale datasets with distinct distributions of teams over skills show state-of-the-art performance, regardless of the underlying graph neural network. For future work, we study cold-start scenarios for new experts and emerging skills with limited historical data, as well as team refinement, where experts in an existing team are replaced to maintain or enhance performance.

## References

- [1] Meltem Aksoy, Seda Yanik, and Mehmet Fatih Amasyali. 2023. Reviewer Assignment Problem: A Systematic Review of the Literature. *J. Artif. Intell. Res.* 76 (2023), 761–827. <https://doi.org/10.1613/JAIR.1.14318>
- [2] Negar Arabzadeh, Sajad Ebrahimi, Sara Salamat, Mahdi Bashari, and Ebrahim Bagheri. 2024. Reviewerly: Modeling the Reviewer Assignment Task as an Information Retrieval Problem. In *Proceedings of the 33rd ACM International Conference on Information and Knowledge Management, CIKM 2024, Boise, ID, USA, October 21–25, 2024*, Edoardo Serra and Francesca Spezzano (Eds.). ACM, 5554–5555. <https://doi.org/10.1145/3627673.3679081>
- [3] Shaked Brody, Uri Alon, and Eran Yahav. 2022. How Attentive are Graph Attention Networks?. In *ICLR*. <https://openreview.net/forum?id=F72ximsx7C1>
- [4] Manoel B. Campêlo, Tatiane Fernandes Figueiredo, and Ana Silva. 2020. The sociotechnical teams formation problem: a mathematical optimization approach. *Ann. Oper. Res.* 286, 1 (2020), 201–216. <https://doi.org/10.1007/S10479-018-2759-5>
- [5] Gonzalo Candel, Victor Sánchez-Anguix, Juan M. Alberola, Vicente Julián, and Vincent J. Botti. 2023. An Integer Linear Programming Model for Team Formation in the Classroom with Constraints. In *Hybrid Artificial Intelligent Systems - 18th International Conference, HAIS 2023, Salamanca, Spain, September 5–7, 2023, Proceedings (Lecture Notes in Computer Science, Vol. 14001)*, Pablo García Bringas, Hilde Pérez García, Francisco Javier Martínez de Pisón, Francisco Martínez-Álvarez, Alicia Troncoso Lora, Álvaro Herrero, José Luis Calvo-Rolle, Héctor Quintián, and Emilio Corchado (Eds.). Springer, 397–408. [https://doi.org/10.1007/978-3-031-40725-3\\_34](https://doi.org/10.1007/978-3-031-40725-3_34)
- [6] Hao Chen, Yuanchen Bei, Qijie Shen, Yue Xu, Sheng Zhou, Wenbing Huang, Feiran Huang, Senzhang Wang, and Xiao Huang. 2024. Macro Graph Neural Networks for Online Billion-Scale Recommender Systems. In *WWW*. 3598–3608. <https://doi.org/10.1145/3589334.3645517>
- [7] Arman Dashti, Saeed Samet, and Hossein Fani. 2022. Effective Neural Team Formation via Negative Samples. In *CIKM*. 3908–3912. <https://doi.org/10.1145/3511808.3557590>
- [8] Arman Dashti, Karan Saxena, Dhvani Patel, and Hossein Fani. 2022. OpeNNTF: A Benchmark Library for Neural Team Formation. In *CIKM*. 3913–3917. <https://doi.org/10.1145/3511808.3557526>
- [9] DBLP. <https://www.aminer.org/citation>
- [10] Yuxiao Dong, Nitesh V. Chawla, and A. Swami. 2017. metapath2vec: Scalable Representation Learning for Heterogeneous Networks. In *SIGKDD*. 135–144.
- [11] Brendan L Douglas. 2011. The weisfeiler-lehman method and graph isomorphism testing. *arXiv preprint arXiv:1101.5211* (2011).
- [12] Edmund H. Durfee, James C. Boerkoel Jr., and Jason Sleight. 2014. Using hybrid scheduling for the semi-autonomous formation of expert teams. *Future Gener. Comput. Syst.* 31 (2014), 200–212. <https://doi.org/10.1016/j.future.2013.04.008>
- [13] José G. M. Esgario, Iago E. da Silva, and Renato A. Krohling. 2019. Application of Genetic Algorithms to the Multiple Team Formation Problem. *CoRR* abs/1903.03523 (2019). <http://arxiv.org/abs/1903.03523>
- [14] Wenqi Fan, Yao Ma, Qing Li, Yuan He, Yihong Eric Zhao, Jiliang Tang, and Dawei Yin. 2019. Graph Neural Networks for Social Recommendation. In *WWW*. 417–426. <https://doi.org/10.1145/3308558.3313488>
- [15] Hossein Fani, Reza Barzegar, Arman Dashti, and Mahdis Saeedi. 2024. A Streaming Approach to Neural Team Formation Training. In *ECIR*, Vol. 14608. Springer, 325–340. [https://doi.org/10.1007/978-3-031-56027-9\\_20](https://doi.org/10.1007/978-3-031-56027-9_20)
- [16] Chen Gao, Yu Zheng, Nian Li, Yinfeng Li, Yingrong Qin, Jinghua Piao, Yuhan Quan, Jianxin Chang, Depeng Jin, Xiangnan He, and Yong Li. 2023. A Survey of Graph Neural Networks for Recommender Systems: Challenges, Methods, and Directions. *Trans. Recomm. Syst.* 1, 1 (2023), 1–51. <https://doi.org/10.1145/3568022>
- [17] Kiarash Golzadeh, Lukasz Golab, and Jarek Szlichta. 2025. Explaining Expert Search and Team Formation Systems with ExES. In *ICDE*. IEEE, 224–237. <https://doi.org/10.1109/ICDE65448.2025.00024>
- [18] William L. Hamilton, Zhitaoying, and Jure Leskovec. 2017. Inductive Representation Learning on Large Graphs. In *Advances in Neural Information Processing Systems: Annual Conference on Neural Information Processing Systems*. 1024–1034.
- [19] Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay S. Pande, and Jure Leskovec. 2020. Strategies for Pre-training Graph Neural Networks. In *ICLR 2020*. <https://openreview.net/forum?id=HJlWwJSDFH>
- [20] Yuntong Hu, Zhihan Lei, Zheng Zhang, Bo Pan, Chen Ling, and Liang Zhao. 2025. GRAG: Graph Retrieval-Augmented Generation. In *NAACL*. 4145–4157. <https://aclanthology.org/2025.findings-naacl.232/>
- [21] Chao Huang, Huance Xu, Yong Xu, Peng Dai, Lianghao Xia, Mengyin Lu, Liefeng Bo, Hao Xing, Xiaoping Lai, and Yanfang Ye. 2021. Knowledge-aware Coupled Graph Neural Network for Social Recommendation. In *AAAI*. 4115–4122. <https://doi.org/10.1609/AAAI.V35I5.16533>
- [22] IMDb. <https://developer.imdb.com/non-commercial-datasets/>
- [23] Sunny Joseph Kalayathankal, John T Abraham, and Joseph Varghese Kureethara. 2019. A Fuzzy Approach To Project Team Selection. *International Journal of Scientific Technology Research* 8 (2019).
- [24] Mehdi Kargar and Aijun An. 2011. Discovering top-k teams of experts with/without a leader in social networks. In *CIKM*. ACM, 985–994.
- [25] Mehdi Kargar, Lukasz Golab, Divesh Srivastava, Jaroslaw Szlichta, and Morteza Zihayat. 2022. Effective Keyword Search Over Weighted Graphs. *IEEE Trans. Knowl. Data Eng.* 34, 2 (2022), 601–616. <https://doi.org/10.1109/TKDE.2020.2985376>
- [26] Sagar Kaw, Ziad Kobti, and Kalyani Selvarajah. 2023. Transfer Learning with Graph Attention Networks for Team Recommendation. In *International Joint Conference on Neural Networks, IJCNN*. 1–8. <https://doi.org/10.1109/IJCNN54540.2023.10191717>
- [27] Bosung Kim, Hyewon Choi, Haeun Yu, and Youngjoong Ko. 2021. Query Reformulation for Descriptive Queries of Jargon Words Using a Knowledge Graph based on a Dictionary. In *CIKM*. 854–862. <https://doi.org/10.1145/3459637.3482382>
- [28] Yue Kou, Derong Shen, Quinn Snell, Dong Li, Tiezheng Nie, Ge Yu, and Shuai Ma. 2020. Efficient Team Formation in Social Networks based on Constrained Pattern Graph. In *ICDE*. 889–900. <https://doi.org/10.1109/ICDE48307.2020.00082>
- [29] Christin Katharina Kreuzt and Ralf Schenkel. 2023. RevASIDE: Evaluation of Assignments of Suitable Reviewer Sets for Publications from Fixed Candidate Pools. *J. Data Intell.* 4, 1&2 (2023), 101–133. <https://doi.org/10.26421/JDI4.1-2-1>
- [30] Solomon Kullback and Richard A Leibler. 1951. On information and sufficiency. *The annals of mathematical statistics* 22, 1 (1951), 79–86.
- [31] Zijian Li, Qingyan Guo, Jiawei Shao, Lei Song, Jiang Bian, Jun Zhang, and Rui Wang. 2025. Graph Neural Network Enhanced Retrieval for Question Answering of Large Language Models. In *NAACL*. 6612–6633. <https://aclanthology.org/2025.naacl-long.337/>
- [32] Poppy L. McLeod, Quinn W Cunningham, Deborah DiazGranados, Gabi Dodoiu, Seth Kaplan, Joann Keyton, Nicole Larson, Chelsea LeNoble, Stephan U Marsch, Thomas A O'Neill, et al. 2021. Hacking teamwork in health care: Addressing adverse effects of ad hoc team composition in critical care medicine. *Health care management review* 46, 4 (2021), 341–348.
- [33] Larry K Michaelsen, Arletta Bauman Knight, and L Dee Fink. 2023. *Team-based learning: A transformative use of small groups in college teaching*. Taylor & Francis.
- [34] Hoang Nguyen, Radin Hamidi Rad, Feras N. Al-Obeidat, Ebrahim Bagheri, Mehdi Kargar, Divesh Srivastava, Jaroslaw Szlichta, and Fattane Zarrinkalam. 2023. Learning heterogeneous subgraph representations for team discovery. *Inf. Retr.* 7, 26, 1 (2023), 8. <https://doi.org/10.1007/S10791-023-09421-6>
- [35] Radin Hamidi Rad, Ebrahim Bagheri, Mehdi Kargar, Divesh Srivastava, and Jaroslaw Szlichta. 2021. Retrieving Skill-Based Teams from Collaboration Networks. In *SIGIR*. ACM, 2015–2019. <https://doi.org/10.1145/3404835.3463105>
- [36] Radin Hamidi Rad, Hossein Fani, Ebrahim Bagheri, Mehdi Kargar, Divesh Srivastava, and Jaroslaw Szlichta. 2024. A Variational Neural Architecture for Skill-based Team Formation. *ACM Trans. Inf. Syst.* 42, 1 (2024), 7:1–7:28. <https://doi.org/10.1145/3589762>
- [37] Radin Hamidi Rad, Hossein Fani, Mehdi Kargar, Jaroslaw Szlichta, and Ebrahim Bagheri. 2020. Learning to Form Skill-based Teams of Experts. In *CIKM*. 2049–2052. <https://doi.org/10.1145/3340531.3412140>
- [38] Radin Hamidi Rad, Aabid Mitha, Hossein Fani, Mehdi Kargar, Jaroslaw Szlichta, and Ebrahim Bagheri. 2021. PyTFL: A Python-based Neural Team Formation Toolkit. In *CIKM*. 4716–4720. <https://doi.org/10.1145/3459637.3481992>
- [39] Pisol Ruenin, Morakot Choetkiertikul, Akara Supratrak, and Suppawong Tu-arob. 2024. TeReKG: A temporal collaborative knowledge graph framework for software team recommendation. *Knowl. Based Syst.* 289 (2024), 111492. <https://doi.org/10.1016/J.KNOSYS.2024.111492>
- [40] Kalyani Selvarajah, Pooya Moradian Zadeh, Ziad Kobti, Mehdi Kargar, Mohd Tazim Ishraque, and Kathryn Pfaff. 2018. Team Formation in Community-Based Palliative Care. In *2018 Innovations in Intelligent Systems and Applications, INISTA 2018, Thessaloniki, Greece, July 3–5, 2018*. IEEE, 1–7. <https://doi.org/10.1109/INISTA.2018.8466272>
- [41] Mauro Sozio and Aristides Gionis. 2010. The community-search problem and how to plan a successful cocktail party. In *SIGKDD*. ACM, 939–948. <https://doi.org/10.1145/1835804.1835923>
- [42] Damjan Strnad and Nikola Guid. 2010. A fuzzy-genetic decision support system for project team formation. *Appl. Soft Comput.* 10, 4 (2010), 1178–1187. <https://doi.org/10.1016/j.asoc.2009.08.032>
- [43] Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. 2018. Graph Attention Networks. In *ICLR*.
- [44] P. Velickovic, W. Fedus, W. L. Hamilton, P. Liò, Y. Bengio, and R. D. Hjelm. 2019. Deep Graph Infomax. In *ICLR*. <https://openreview.net/forum?id=rklz9iAcKQ>
- [45] Lin Wang, Yifeng Zeng, Bilian Chen, Yinghui Pan, and Langcai Cao. 2020. Team Recommendation Using Order-Based Fuzzy Integral and NSGA-II in StarCraft. *IEEE Access* 8 (2020), 5959–5970. <https://doi.org/10.1109/ACCESS.2020.2982647>
- [46] Menghan Wang, Yujie Lin, Guli Lin, Keping Yang, and Xiao-Ming Wu. 2020. M2GRL: A Multi-task Multi-view Graph Representation Learning Framework for Web-scale Recommender Systems. In *SIGKDD*. 2349–2358. <https://doi.org/10.1145/3394486.3403284>
- [47] Ruijie Wang, Yutong Zhang, Jinyang Li, Shengzhong Liu, Dachun Sun, Tianchen Wang, Tianshi Wang, Yizhuo Chen, Denizhan Kara, and Tarek F. Abdelzaher. 2024. MetaHKG: Meta Hyperbolic Learning for Few-shot Temporal Reasoning. In *SIGIR*. 59–69. <https://doi.org/10.1145/3626772.3657711>

- [48] Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S. Yu. 2019. Heterogeneous Graph Attention Network. In *WWW. ACM*, 2022–2032.
- [49] Hyeongon Wi, Seungjin Oh, Jungtae Mun, and Mooyoung Jung. 2009. A team formation model based on knowledge and collaboration. *Expert Syst. Appl.* 36, 5 (2009), 9121–9134. <https://doi.org/10.1016/j.eswa.2008.12.031>
- [50] Keyulu Xu, W. Hu, Jure Leskovec, and S. Jegelka. 2019. How Powerful are Graph Neural Networks?. In *ICLR*. <https://openreview.net/forum?id=ryGs6iA5Km>
- [51] Armen Zakarian and Andrew Kusiak. 1999. Forming teams: An analytical approach. *IIE Transactions* 31 (01 1999), 85–97. <https://doi.org/10.1023/A:1007580823003>
- [52] Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal A. C. Xhonneux, and Jian Tang. 2021. Neural Bellman-Ford Networks: A General Graph Neural Network Framework for Link Prediction. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems. 29476–29490*. <https://proceedings.neurips.cc/paper/2021/hash/f6a673f09493afcd8b129a0bcf1cd5bc-Abstract.html>